



HUB

02400

The hub is a foundational component of intelligent infrastructure and allows fire equipment to be accessible through service-dashboards, monitoring, alarm-notifiers, service applications, and 3rd party integrations. Supports multiple radio protocols and mesh configurations.





Basic	DIMENSIONS 140 x 80 x 28 mm	WEIGHT 113 g
	COLOR White	
	MATERIALS Polymer	INGRESS PROTECTION IP 20
	OPERATING TEMPERATURE -10°C to + 50°C	OPERATING HUMIDITY Up to 75% non-condensing
Technical	POWER SUPPLY 5 VDC, 1A USB-C type connector	
	INTERNET CONNECTIVITY: Wi-Fi security level: WEP, WPA, WPA2 (personal) Range in free field:>300m Frequency: 2400-2495 MHZ Max. transmit power: 20 dBm	WIRELESS CONNECTIVITY: Setup through Bluetooth LE V4.2 Range in free field:>10m Frequency: 2400-2483.5 MHZ Max. transmit power: 9 dBm
	COMMUNICATIONS: Protocol: Proprietary wireless protocol Range in free field:>300m Frequency: 868 MHz Max. transmit power: 14 dBm AES-128	CYBER SECURITY STANDARDS Adheres to ETSI EN 303 645 V2.1.1 (2020-06) OTA, encrypted flash, secure boot, e-fuses, TLS



Certifications

CE

RoHS

ETSI EN

Other information

MANUFACTURED
In P.R.C.

DESIGNED BY
COSESY A/S
Viengevej 100
8240 Risskov
Denmark